



2025 MODIFIED DIMENSIONS

- A)** Window opening-12"min-18"max.
- B)** Front edge of roof to interior deck-11"min.
- C)** Rear edge of roof to interior deck-12"min.
- D)** Highest point of roof to ground-42"min-52"max.
- E)** Center of front wheel to front edge of front bumper-42".
- F)** Wheelbase: center of rear wheel to center of front wheel-108"min-112"max.
- G)** Center of rear wheel to front edge of door-72"max.
- H)** Center of rear wheel to rear edge of quarter panel-34"min-47max.
- I)** Center of lowest bar on rear bumper to ground-16-20"max.
- J)** Deck height to ground-28"min-38"max.
- K)** Rear sail panel height 4"max.
- L)** Sail panel curve from rear of roof to rear of panel-2"max.
- M)** Sail panel bow from bottom to roof-2"max.
- N)** 2" max lip, same on both sides flush with hood.
- O)** 5" max drop (sides) sealed off from driver's compartment and max 6" rake.
- P)** 42" max nose must be flat and flush with sides.
- Q)** 67" max 42" min, must cover radiator
- R)** 53" max 32" min
- S)** 53" max 32" min
- T)** 67" max 55" mini, measured at top of interior deck, must be same from back to front. Back of quarter panels 72" Max (measured at the bottom)
- U)** Width at the bottom of the doors (measured in front of rear tires) 72" Max

